

SPECIFICATIONS

Make		FUSO
Range		FA
Model		FA9-137L
Model Code		FAV1PK1RBSA
Axle Layout		4X2
Cab		Forward Control
Crew		3 seating
Vehicle type		Freight Carrier
Mass Data (kg)		
GVM	Manufacturer's gross vehicle mass	9600
GCM	Manufacturer's gross combination mass	9600
D/T	Permissable max towing drawing vehicle mass	9600
GA-Front	Manufacturer's front axle mass	3510
GA-Rear	Manufacturer's rear axle mass	6520
V	Permissable maximum vehicle mass	9600
AF	Permissable maximum front axle mass	3510
AR	Permissable maximum rear axle mass	6520
UF	Unladen front axle mass	2070
UR	Uladen rear axle mass	1240
UT (Tare)	Total unladen mass	3310
Permissible Body +	Payload	6290
Fuel Tank (Litres)	Capacity	200
Dimensions (mn	n)	
OL	Overall length	8195
OW	Overall width	2200
CA	Cab to Axle	4275
OH	Overall height	2390
FOH	Front overhang	1275
ROH	Rear overhang	2120
WB	Wheelbase	4800
Performance		
Maximum Running Gradeability (%)		29.0%
Maximum Speed (SA Legislation)		80 km/h
Minimum turning radius 8.8		
Standard Equip	ment/features	'
12V Accessory Pow Radio AM/FM + USE Central Locking Electrical Windows Intelligent instrument	em Cap and Fuel Theft Protection er Outlet 3 + Aux t Cluster (DTE, Fuel Economy, Engine Run Hours) LH Front and side Safety Mirrors	

Variable Engine HPM Control
E-Viscous Fan
Telescopic and Tilt Steering Column with Steering lock
Additional Roof Storage
Fully trimmed Cabin
LED Lamps
Pendant Type Brake Pedal
Cab Coloured Bumper

Standard Services

4 Years / 240 000 km warranty

20 000km maintenance schedule

Engine			
Make	FUSO		
Model	4D37		
Configuration	Diesel inline 4		
Capacity (cm3)	3907		
Туре	4-stroke, water cooled direct injection, turbocharged diesel engine		
Power at RPM	100 @ 2500 - 2500		
Torque at RPM	420 @ 1500 - 1500		
Emission standards	Euro 3		
Generator	24 V / 45 A		
Air Cleaner	Dual filter, paper element mechanical chock, indicator		
Suction	Snorkel and rain cap		
Governor	Electrical control type		
Transmission			
Make	FUSO		
Model	MO36S6		
Туре	Synchromesh gears		
Shift	Manual		
No. of gears forward	6		
First gear ratio	5.4		
Top gear ratio	0.711		
Clutch			
Make	FUSO		
Model	C3W28		
Туре	Hydraulic Single Dry Plate		
Diameter (mm)	330		
Drive Axle			
Reduction type	Fully Floating, Single Reduction		
Final Ratio	5.13		
Suspension			
Front	Semi Elliptic-multi leaf spring with shock Absorbers and Anti Roll Bar		
Rear	Semi Elliptic-multi leaf spring with shock Absorbers		
Steering			
	Hydraulic Integral Power Assisted		
Brakes			
System type	Pneumatic, Foot operated, Dual line acting on all wheels		
Front	Drum		
Rear	Drum		
ABS	Yes		
Park/Emergency System	Yes		
Auxiliary Brakes	Exhaust brake		
Tyres and Rims			
Tyre Sizes	235 / 75 R 17.5		
Wheel type	Drum Type		
Electrical			
System	24V		

Details not binding - subject to change without notice 03/2021



DIMENSIONS www.fuso.co.za









