

SPECIFICATIONS

FJ26-280R SLEEPER

| Make | | FUSO |
|----------------------------------------------------------------|------------------------------------------------------------------|-------------------|
| Range | | FJ |
| Model | | FJ26-280R SLEEPER |
| Model Code | | FJY1WT2RBSA |
| Axle Layout | | 6x2 |
| Cab | | Sleeper Cab |
| Crew | | 3 seating |
| Vehicle type | | Rigid |
| Mass Data (kg) | | |
| GVM | Manufacturer's gross vehicle mass | 26500 |
| GCM | Manufacturer's gross combination mass | 34000 |
| D/T | Permissible max towing drawing vehicle mass | 34000 |
| GA-Front | Manufacturer's front axle mass | 7500 |
| GA-Rear | Manufacturer's rear axle mass | 19000 |
| V | Permissible maximum vehicle mass | 25500 |
| AF | Permissible maximum front axle mass | 7500 |
| AR | Permissible maximum rear axle mass | 18000 |
| UF | Unladen front axle mass | 4040 |
| UR | Unladen rear axle mass | 3760 |
| UT (Tare) | Total unladen mass | 7800 |
| Permissible Body + Payload | | 17700 |
| Fuel Tank (Litres) | Capacity | 380+200 |
| Dimensions (mm) | | |
| OL | Overall length | 11995 |
| OW | Overall width | 2490 |
| CA | Cab to Axle | 5555 |
| OH | Overall height | 2985 |
| FOH | Front overhang | 1460 |
| ROH | Rear overhang | 3485 |
| WB | Wheelbase | 6375 |
| Performance | | |
| Gradeability at Permissible Maximum Weight (V) | | 50%/33% |
| Maximum Speed (SA Legislation) | | 80 km/h |
| Minimum turning radius | | 12.6 m |
| Standard Equipment/features | | |
| Arctic White (AW1) | Variable RPM Control | |
| All Steel Forward Control Tilting Day Cab | Cruise Control | |
| Air Suspended Driver's Seat with integral Seat Belt | Engine Brake & Exhaust Brake | |
| ELR 3-Point with Centre Lap Belt & Driver's Seat Belt Reminder | E-viscous Fan (Intermittent operation fan improves fuel economy) | |
| Air Conditioner / Heater / Demister | Differential Lock Buzzer | |
| 12V Accessory Power Outlet | Clutch Wear Indicator (Preventative Maintenance) | |
| Radio AM/FM + USB + AUX | Day Time Running Lights (LED) | |
| Central Locking and Electric Windows | Intelligent Instrument Cluster with On-board Diagnostic | |
| Speedometer, Tacho, Air and Fuel Gauges | Anti Roll / stabilizer Bars (Front and Rear) | |
| Dual Door Mirrors + LH Front and Side Safety Mirrors | | |
| Standard Service | | |
| 4 Years / 300 000 km warranty | | |
| 15 000 km / 20 000 km / 25 000 km maintenance schedule | | |

| Engine | |
|-----------------------|--------------------------------------------------------------------|
| Make | FUSO |
| Model | 6S20 205 |
| Configuration | Diesel inline 6 |
| Capacity (cm3) | 6373 |
| Type | Four stroke water cooled direct injection diesel engine |
| Power at RPM | 205 kW @ 2200 rpm |
| Torque at RPM | 1100 Nm @ 1200 rpm to 1600 rpm |
| Emission standards | Euro III |
| Generator | 24V, 80A |
| Air Cleaner | Dry type – Twin Stage, Paper element |
| Suction | Snorkel and rain cap |
| Governor | Electrical control type |
| Transmission | |
| Make | FUSO |
| Model | G131 |
| Type | Synchromesh gears |
| Shift | Manual |
| No. of gears forward | 9 |
| First gear ratio | 14.57 |
| Top gear ratio | 1 |
| Clutch | |
| Make | FUSO |
| Model | - |
| Type | Dry-Single plate, Hydraulic actuated control with servo assistance |
| Diameter (mm) | 395 |
| Drive Axle | |
| Make | FUSO |
| Reduction type | Full Floating Type, Single Reduction, Hypoid Gears |
| Final Ratio | 4.3 |
| Suspension | |
| Front | Parabolic leaf spring |
| Rear | Semi elliptic – Auxiliary spring |
| Stabilisers | Yes |
| Steering | |
| | Power assisted – Hydraulic |
| Brakes | |
| System type | Pneumatic |
| Front | Drum |
| Rear | Drum |
| ABS | Yes |
| Park/Emergency System | Pneumatically operated Spring actuated with hand brake |
| Auxiliary Brakes | Engine brake & Exhaust brake |
| Tyres and Rims | |
| Tyre Sizes | 315 / 80R 22.5 |
| Wheel type | Radial, Tubeless |
| Electrical | |
| System | 24V |

Details not binding - subject to change without notice 03/2021

